

## FEATURES

- ◆ Built-in Transformers
- ◆ U-mount Brackets Included
- ◆ “Ferofluid” Cooled Tweeters
- ◆ Injection molded ABS Cabinet

## APPLICATIONS

- ◆ Weather Resistant
- ◆ Retail Outlets
- ◆ Restaurants
- ◆ Lounges
- ◆ Patios
- ◆ Health Clubs
- ◆ Conference Rooms



## DESCRIPTION

The EFG802 is a completely self-contained coaxial, bass-reflex speaker system. The largest of the Enforcer indoor/outdoor loudspeakers, its characteristic bright and clean sonance makes it a staple item for medium to large retail outlets that demand quality reproduction for sales announcements and clear delivery of foreground/background music.

The EFG802 is housed in a 2-way injection molded ABS box cabinet with 8” mica cone, rubber surround woofers. The tweeters are ferrofluid cooled. Ferrofluids are injected into the gap to help maintain the voice coil at much cooler temperatures. This provides the EFG series much greater power handling ability. A built-in 70-volt transformer offers a variable tap selection switch and a transformer bypass for 8-ohm operation.

Available in white or black with aluminum grill and mounting u-brackets, the EFG802 can be painted or re-finished to match any décor. Optional swivel mounts (model EBK8) are also available.

Durable and weather resistant, wiring terminations are enclosed in a five-way binding post located at the rear of the speaker housing allowing for spade lugs, banana plugs or bare wire installation options. However, optimal results are achieved with oversized spade lugs.

## SPECIFICATIONS

Electronic	
Woofers	8” Mica Cone Rubber Edge
Magnet	20 oz.
Tweeter	13mm Mylar dome w/ 1.49 oz. Magnet
Frequency Response	40-20,000 Hz
Power Handling	75 Watts RMS, 120 Watts Program
Impedance	8Ω or 70 Volt/100Volt
Transformer Taps	50W, 25W, 10W, 5W, 8Ω

Hardware	
Dimensions	27.3cmW x 36.2cmH x 21cmD 10.75”W x 14.25”H x 8.25”D, depth with bracket 9.78”
Weight	14.51Kgs (32 lbs.)
Cabinet	Injected ABS
Grill	Aluminum/Powder Coat Paint
Bracket	Aluminum/Powder Coat Paint



# EFG8020D

INDOOR/OUTDOOR BACKGROUND/FOREGROUND SPEAKER

---

## ARCHITECTURAL SPECIFICATIONS

---

The surface mount speaker system shall be an Enforcer EFG8020D Series with a frequency response of 40Hz / 20kHz  $\pm$  10 db half space. The speaker utilizes an injection molded ABS cabinet, with an 8" Mica woofer, 1/2" Mylar dome tweeter and 70/100 volt transformer with a built in tap selector switch. Tap settings @ 5W, 10W, 25W, 50W and must include a transformer bypass position for direct use. With an RMS rating of 80 watts, this speaker system must be supplied with all mounting hardware, which consists of aluminum U mounting brackets powder coated to match the cabinet color (white or black). The grill must be manufactured from aluminum and powder coated to match. This treatment should assure the product will not rust if used outdoors. The enclosure must have the following dimensions: 10.75" W X 14.25" H X 8.25" D. This speaker system must be part of a complete family series with additional sizes in 5" and 6" speaker versions.

---

Supplying Dealer